

## CH15MS Flameless Heater

The CH15MS industrial heater uses a patented magnetic heat generating technology. The CH15MS can be thermostatically controlled, allowing you to set the temperature and CFM output to carry out crucial heating operations.

### Features

- 1.5 million BTU equivalent
- Thermostatically controlled
- 200° F temperature rise
- Up to 7200 CFM
- 14" above WC static pressure
- 110% secondary containment
- CSA Field certified
- Self-contained unit with no external power source required
- Positive air shutoff
- Clean, breathable air
- Rugged design for increased durability



*A CH15MS heater heating multiple BOPs simultaneously using split ducting on an oilfield*

### Applications

- Drill deck, pump station and water line heating
- Snubbing stack heating
- Heating wellheads and BOPs
- Equipment thawing and deicing

#### Oil and Gas



- Concrete curing
- Ground thaw
- Aggregate Heating
- Worker Comfort Heating
- Multi-story construction heating

#### Construction



- Tank coating and curing
- Surface Preparation
- Moisture and humidity control
- Dehumidification
- Deicing
- Auxiliary heat

#### Coating and Painting





*A CH15MS heater curing a large concrete section on a construction project*



*Delivering hot, dry, air to control humidity and temperature while coating a large tank*

## Technical specifications

### Performance

<b>BTU rating</b>	1.5 million
<b>CFM range</b>	1500 - 7200
<b>Static Pressure</b>	14' above WC

### Fuel Data

<b>Fuel Capacity</b>	235 gallons
<b>Fuel Type</b>	ULSD diesel
<b>Fuel Consumption</b>	3.5-8.5 gph

### Engine Data

<b>Type</b>	John Deere 6068 HF385 or Cummins
<b>Oil Type</b>	15W 40 / 8gallons

### Dimensions

Height	Length	Width	Dry Weight
8'	14'9"	6'10"	8440 lbs

### Additional Features

- GPS tracking for location and runtime
- Strobe Operating light
- Low Fuel shutdown
- Guaranteed runtime of 24 hours between fueling
- Trailer hitch 2 5/16" Ball or Pintle

With our 24x7 service response model, we strive to eliminate downtime and guarantee fastest service turnaround.

The CH15MS heaters are available for SALES and RENTAL

**For inquiries, please call us at 1.844.900.5465 or email us at [sales@northlinksupply.ca](mailto:sales@northlinksupply.ca)**